



FD/G Series 15-18 Counter Balanced Forklift



Wide view mast VM

Mast model	Load center 500mm		Max.lift height	Mast height		Tilt range	(3) Weight	
	FG/D 15T	FG/D 18T		fork lowered	(1) fork lift with backrest		FG 15T	FG 18T
	kg	kg		mm	mm		mm	mm
VM250	1500	1750	2500	1745	3530	6 - 12	2490	2710
VM270	1500	1750	2700	1845	3730	6 - 12	2505	2725
VM300	1500	1750	3000	1995	4030	6 - 12	2520	2740
VM330	1500	1750	3300	2145	4330	6 - 12	2540	2760
VM350	1500	1750	3500	2245	4530	6 - 12	2550	2770
VM375	1500	1750	3750	2370	4780	6 - 6 * 6 - 12	2565	2785
VM400	1500	1650 *1750	4000	2545	5030	6 - 6 * 6 - 12	2610	2830
VM425	1400 * 1500	1500 *1750	4250	2670	5280	6 - 6 * 6 - 12	2625	2845
VM450	1400 * 1400	1500 *1650	4500	2795	5530	6 - 6 * 6 - 12	2640	2860
VM475	1000 * 1350	1000 *1500	4750	2920	5780	6 - 6 * 6 - 6	2655	2875
VM500	1000 * 1350	1000 *1500	5000	3045	6030	6 - 6 * 6 - 12	2665	2885
VM550	* 1100	*1300	5500	3345	6530	* 3 - 6	2835	3055
VM600	* 800	*1100	6000	3595	7030	* 3 - 6	2865	3085

2 stage free lift mast VFM

Mast model	Load center 500mm		Max.lift height	Mast height		(2) free lift with backrest	Tilt range	(3) Weight	
	FG/D 15T	FG/D 18T		fork lowered	(1) fork lift with backrest			FG 15T	FG 18T
	kg	kg		mm	mm			mm	mm
VFM250	1500	1750	2500	1745	3530	735	6 - 12	2550	2770
VFM270	1500	1750	2700	1845	3730	835	6 - 12	2560	2780
VFM300	1500	1750	3000	1995	4030	985	6 - 12	2580	2800
VFM330	1500	1750	3300	2145	4330	1135	6 - 12	2605	2825
VFM350	1500	1750	3500	2245	4530	1235	6 - 12	2615	2835
VFM375	1500	1750	3750	2370	4780	1360	6 - 6 * 6 - 12	2635	2855
VFM400	1500	1750	4000	2545	5030	1535	6 - 6 * 6 - 12	2680	2900

3 stage free lift mast VFHM

Mast model	Load center 500mm		Max.lift height	Mast height		(2) free lift with backrest	Tilt range	(3) Weight	
	FG/D 15T	FG/D 18T		fork lowered	(1) fork lift with backrest			FG 15T	FG 18T
	kg	kg		mm	mm			mm	mm
VFHM360	1400	1600	3600	1745	4630	735	6 - 6	2670	2890
VFHM400	1400	1600	4000	1870	5030	860	6 - 6	2695	2915
VFHM435	1350 * 1400	1550 * 1600	4350	1995	5380	985	6 - 6 * 6 - 6	2720	2940
VFHM480	1300 * 1350	1400 * 1550	4800	2145	5830	1135	6 - 6 * 6 - 6	2745	2965
VFHM500	1100 * 1300	1150 * 1500	5000	2245	6030	1235	6 - 6 * 6 - 6	2765	2985
VFHM540	850 * 1250	900 * 1400	5400	2370	6430	1360	3 - 6 * 3 - 6	2790	3010
VFHM600	500 * 1100	500 * 1250	6000	2595	7030	1585	3 - 6 * 3 - 6	2860	3080

Note: (1) Max.lift height (without backrest):-470mm (2) Free lift height without backrest:+470mm; Weight without backrest:-15kg; (3) Weight of diesel forklift:+30kg(FD15T) ,+40kg(FD1.8T)
The mark of * is with double tires



Folangsi Machine Co., Ltd.

Tel: +86 020-3999 3595 Fax: +86 020-3999 3597

E-mail: admin@folangsiforklift.com

Address: No.13 Bangyan Road,
Panyu District, Guangzhou, China

Distributor:

Three Features



1 Cleaner, more efficient Engines

New engines, compliant with worldwide stage IIIA emission regulations (ISUZU C240PKJ Diesel powered engine)

2 Easy Maintenance

Detachable side covers for convenient inspection and simple maintenance. Integral layout of electrical parts and other system devices.



3 Easier entry and exit form an extra-wide step

The secure step with enlarged foot space enables greater comfort and less fatigue while entering and exiting the vehicle.

